

## **Product Datasheet**





## Mini Recorder

#### **ABOUT**

The Mini recorder is the worlds' smallest fully featured PACE compliant interview recorder.

It is supplied with a monitor mount bracket, pre-wired cable for third party input, a remote control device and power supply.

#### **FEATURES**

- · All in one design
- 3 ch. video input
- AES256 Encryption
- SHA256 digital signature
- Integrated battery backup to prevent data corruption/loss
- User friendly
- 4 hour continuous recording on battery
- Compatible with: Hub



# **Product Datasheet**

## Mini Recorder

Input		
Video Input	BNC AHD Camera input	External video input allows third camera to be connected if required, e.g., interpreter, or captures computer screen using HDMI to AHD converter (not supplied).
Microphone	2 x Internal 1 x 6 pin Hirose connector	Two internal microphones offer backup if external microphone is not used or fails.
Formats and S	torage	
Audio	Video Mode = AAC Audio Only Mode = MP3	Non-proprietary formats for integration to third party solutions.
Video	H.265 High efficiency Video Coding (multiple rates).	Offers the best format to maximise resolution and minimise storage requirements. Non-proprietary for integration to third party solutions.
Storage	Internal = 64GB eMMC Flash External = MicroSD/USB	Records master copy internally for upload and offers options for removable copy.
Network		
Security	AES256 Encryption	Protects data on device while outside of a secure environment.
Integrity	SHA256# Digital Signature	Provides chain of evidence from point of capture through to presentation in court.
Wi-Fi	150Mbs 802.11b,g,n	Can be enabled or disabled. If enabled can offer remote upload and/or APP interface for meta data entry, remote streaming, and remote control.
RJ45	High Speed 10/100 Ethernet	Offers upload of files, live streaming, and remote setup/diagnostics.
USB	USB 2.0	Offers interface for USB backup or DVD Backup.
General		
Power	12V DC Input (Standard) Battery 4-5 hours recording	Versatile power options.
GPIO	8 Pin	External controller or third camera to be connected if required e.g interpreter, or captures computer screen using HDMI to AHD converter (not supplied).
LED	2 x LED Record and Monitoring Indicator	Visual indicator when in record and a second to show when being monitored
Audit	Read-only access full audit trail.	
Dimensions	139 x 135 x45mm including rear connectors (133mm excluding connectors).	
Weights	500g	Recorder only